Compare Adhesive-free Flooring Installation System - IOBAC MagTabs™ MT4+

Verified by manufacturer 2 months ago

The adhesive-free flooring installation system for carpet, LVT, and woven vinyl flooring.

Jump to:

- Specification data
- Environmental information

Add to spec



Application

Suitable to affix carpet tiles, +4mm luxury vinyl tiles (LVT) and woven vinyl onto receptive bases, including:

- Metal raised access floors.
- IOBAC Ezy-Install® Magnetically Receptive Underlay.
- IOBAC Magnetically Receptive Resins.

Approved for installation of carpet tiles, Luxury Vinyl Tiles and woven vinyl from leading flooring brands including Shaw Contract EMEA, Milliken, Balsan, Bolon, Ntgrate, Burmatex, BLOQ, Forbo, Ege Carpets, Tarkett and Desso in multiple projects.

Description

For Reusable Flooring That's Hard to Shift, Easy to Lift

MT4+ MagTabs combine dry-tack with magnetism to easily and securely affix carpet tile, LVT and woven vinyl flooring.

They ensure that flooring is easy to remove when needed leaving no adhesive contamination, so that:

> Flooring tiles can be easily re-used or recycled, contributing to manufacturers' take-back schemes and improving the circularity of flooring materials

> The sub-floor is kept clean and contamination-free and is immediately ready for the next installation

Features and benefits:

- **SECURE:** Dual-Grip hold ensure outstanding grip across multiple floor covering types.
- **SUSTAINABLE:** Adhesive-free means flooring can be cleanly uplifted, reused or recycled.
- CLEAN: Removal of all VOC related adhesives.
- **FAST:** Simple installation method, flooring is immediately ready for traffic.
- **FLEXIBLE:** Easy uplift for access, repair and design changes.
- **COST-EFFECTIVE:** Base is left clean minimal rectification needed before next install.

General information

Color	Black
Shape	Square
Length	97 mm
Width	97 mm
Height	0.3 mm
Uniclass	Pr_35_90_87_50 Magnetic adhesive-backed tapes Primary
CAWS	M50/130 Carpet tiling M50/110 Resilient floor tiling M50/15 Carpet tiling M50/10 Resilient floor tiling

Specification data - Magnetic adhesive-backed tapes

Dimensions Tab dimensions.	97 x 97 mm.
Thickness	0.3 mm.
Form	Self-adhesive magnetic tabs.
Colour	Black.
Colour	
Environmental inform	nation
	No
Environmental inform	
Environmental inform Contains Red List materials	No United Kingdom